

BIND-AP67

Acrylic polyurethane binder

Chemical composition	Acrylic polyurethane blend
Appearance	Milky white emulsion
Solids	36% +/-2
Charge	Anionic
pH 10%	5.0 - 7.0

Application:

- **BIND-AP67** gives clear colorless and flexible film.
- Excellent Penetration properties and cold crack resistance.
- Outstanding Wet and Dry Rub Fastness.
- Maintains soft touch and natural look.
- Can be used in Base Coats, intermediate coats in finishing of shoe softy, uppers, garments, gloves and milled articles.

<u>Usage:</u>

Recommended 50 to 100 Parts in base coats and intermediate coats.

Note: The product being combination of various raw materials, there are chances of variations in colour and viscosity. The property and Application of the product will remain same.

The above information on application on leather is given in accordance to the best of our knowledge and our lab applications. As the usage of the product by the consumer is not under our control, we are not liable for any sort of claims or reimbursements. The product is given without any guarantee/warranty in connection to end use.



COMP-BW

Anionic Compact

Chemical composition	Based on Multiple finishing system
Appearance	Pale Beige Fluid
Solids	24 to 26%
Charge	Anionic
pH 10%	7.0 - 8.5

Application:

COMP-BW is a special formulated product which gives good covering with smooth handle and best anchoring of the finish.

It is suitable for full grain articles, corrected grain, uppers and defect covering system. Provides excellent covering of defects with remarkable sealing of defects.

Excellent light fastness and hence can be used in wet white and other light fast and pastel finishes. Can be applied with spray and also by roller coating.

Usage:

Normally 50 to 100 parts in season combination will result in remarkable upgradation.

Note: The product being combination of various raw materials, there are chances of variations in colour and viscosity. The property and Application of the product will remain same.

The above information on application on leather is given in accordance to the best of our knowledge and our lab applications. As the usage of the product by the consumer is not under our control, we are not liable for any sort of claims or reimbursements. The product is given without any guarantee/warranty in connection to end use.



WAX RM Season Wax Emulsion

Chemical composition	Based on synthetic waxes & special fillers
Appearance	Off-white to creamish fluid
Solids	20% +/-2
Charge	Anionic
pH 10%	7.0 - 8.0

Application:

- WAX RM provides leather with smooth touch.
- Enhances and helps the possibility of high temperature plating.
- In season coting it will improve the surface filling.

Usage:

As per the desired need.

Note: The product being combination of various raw materials, there are chances of variations in colour and viscosity. The property and Application of the product will remain same.

The above information on application on leather is given in accordance to the best of our knowledge and our lab applications. As the usage of the product by the consumer is not under our control, we are not liable for any sort of claims or reimbursements. The product is given without any guarantee/warranty in connection to end use.